



FingerTec
OFIS-X



SPECIFICATIONS

MODEL	OFIS-X
ALGORITHM	BioBridge VX 9.0 / BioBridge VX 10.0
SUPPORTING OS	32-bit Windows XP, Windows Vista, Windows 7
PIXEL RESOLUTION, DPI	512 dpi (average x, y over the scanning area)
SCAN CAPTURE AREA, MM	17mm (width at the center) x 26 mm (length)
SCAN DATA	8-bit grayscale (256 levels of gray)
READER SIZE (APPROXIMATE)(L X W X H), MM	87 x 58 x 24
COMPATIBILITY	USB 1.0, 1.1 and 2.0 (full speed) specifications
OS/BROWSER	MS Windows/ MS Internet Explorer (IE 9)
POWER SUPPLY	5.0V +/- 0.25V USB supply
SUPPLY CURRENT – SCANNING	100mA (typical)
SUPPLY CURRENT – IDLE MODE	30mA (typical)
SUPPLY CURRENT – SUSPEND MODE	0.5mA (max)
ESD SUSCEPTIBILITY	>15kV, mounted in case
OPERATING TEMPERATURE (°C)	0 – 55
OPERATING HUMIDITY (%)	20 – 80 non-condensing
STANDARD FCC CLASS	FCC Class B, CE, USB
USAGE	Indoor, home and office use

NOTE: Specifications are subject to change. Check <http://product.fingertec.com> for latest product information.